



H.M.I.S.	
H -	2
F -	4
R -	0
P.P.	

BRIGHT ZINC COLD GALVANIZING COMPOUND

STOCK # ('S): 17044

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURE: ANTI-SEIZE TECHNOLOGY

2345 N. 17th. Ave.

FRANKLIN PARK, IL. 60131

TELEPHONE #: 847-455-2300

24 HR. EMERGENCY #: INFOTRAC @ 1-800-535-5053

SECTION II - COMPOSITION

	CAS #	OSHA PEL,	TLV	SARA III	PROP 65,	PERCENT
ZINC	7440-66-6	100ppm	100ppm	YES	NO	20 - 40
ALUMINUM	7429-90-5	100ppm	100ppm	NO	NO	1 - 10
ALIPHATIC PETROLEUM DISTALLATES	8052-41-3	100ppm	100ppm	NO	NO	1 - 10
XYLENE	1330-20-7	50ppm	25ppm	YES	YES	1 - 10
ACETONE	67-64-1	100ppm	100ppm	NO	NO	20 - 30
TOLUENE	108-88-3	100ppm	100ppm	NO	NO	1 - 10
DIACETONE ALCOHOL	123-42-2	50ppm	50ppm	NO	NO	1 - 10
PROPANE / ISOBUTANE	74-98-6	1000ppm	1000ppm	NO	NO	5 - 15

SECTION III - PHYSICAL PROPERTIES

BOILING POINT: - 40 - 385 F

MELTING POINT: DOES NOT APPLY

VAPOR DENSITY (AIR = 1): 4.0

EVAPORATION RATE (BUTYL ACETATE = 1): < 1

APPEARANCE AND ODOR: GRAY, SOLVENT ODOR,

SOLUBILITY IN WATER: NIL

REACTIVITY IN WATER: NONE

SPECIFIC GRAVITY: 1.1

SECTION IV - FIRE AND EXPLOSION DATA

AEROSOL FLAMMABILITY: EXTREMELY FLAMMABLE

FLAMMABLE LIMITS: LEL: 1.8 UEL: 12.0

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: CANS MAY RUPTURE, BURST OR EXPLODE IN A FIRE. USE EXTREME CAUTION. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP. WEAR GOGGLES AND A SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CANS MAY RUPTURE OR BURST, RELEASING THEIR CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

SECTION V- PHYSICAL HAZARDS

STABILITY: (X) STABLE () UNSTABLE

CONDITIONS TO AVOID: APPLICATION TO HOT SURFACES, STORAGE ABOVE 120F. EXPOSURE TO OPEN FLAMES.

INCOMPARABILITY ,(MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARDS AND FIRST AID

ROUTES OF ENTRY: SKIN EYES INHALATION INGESTION

HEALTH HAZARDS: READ THE WARNING LABELS ON THE CAN FOR ADDITIONAL INFORMATION.

THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE HEALTH REACTION WHEN USED UNDER NORMAL CONDITIONS. THE SOLVENTS CONTAINED IN THIS PRODUCT HAVE BEEN KNOWN TO EFFECT THE CENTRAL NERVOUS SYSTEM IF THE CONCENTRATION IS HIGH ENOUGH. USE WITH ADEQUATE VENTILATION, LOCAL EXHAUST OR RESPIRATOR TO MAINTAIN THE AIR QUALITY. SYMPTOMS OF OVEREXPOSURE COULD INCLUDE DIZZINESS, HEADACHE, SKIN IRRITATION OR NARCOSIS.

EMERGENCY FIRST AID PROCEDURES

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH . PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES: FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION: NOT A LIKELY ROUTE OF EXPOSURE, DO NOT INDUCE VOMITING, . USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION: THE SOLVENTS AND/OR PROPELLANTS IN THIS PRODUCT MAY EFFECT THE RESPIRATORY TRACT OR CENTRAL NERVOUS SYSTEM. AVOID OVEREXPOSURE. DIZZINESS OR RESPIRATORY IRRITATION ARE SIGNS OF OVEREXPOSURE. SEEK FRESH AIR. OR FOLLOW OTHER STANDARD MEDICAL PRACTICES..

CHEMICAL ('S) LISTED AS CARCINOGENS

NPT ?: NO **I.A.R.C. ? :** NO **OSHA ? :** NO

SECTION VII - SPECIAL PRECAUTIONS AND SPILL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL ,WELL VENTILATED AREA. DO NOT STORE ABOVE 120 F. .

OTHER PRECAUTIONS: DO NOT TAMPER WITH VALVE. DO NOT PUNCTURE, DO NOT SPAY IN EYES OR INGEST, READ THE PRODUCT LABEL FOR ADDITIONAL INFORMATION. KEEP AWAY FROM CHILDREN.

SPILL/ LEAKAGE PROCEDURES: AVOID BREATHING VAPORS. VENTILATE AREA AND REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN A CLOSE CONTAINER FOR DISPOSAL..

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. REFER TO OTHER SECTIONS OF THIS MSDS FORM FOR ADDITIONAL INFORMATION

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE A LOCAL EXHAUST TO REMOVE VAPORS, AND MAINTAIN AIR QUALITY. IF TLV'S ARE ABOVE ACCEPTABLE LIMITS USE A SELF CONTAINED BREATHING APPARATUS.

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED

EYE PROTECTION: SAFETY GLASSES WITH SIDE SPLASH SHIELDS ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

SECTION X - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65: NO

OZONE DEPLETING SUBSTANCES: NO

SARA TITLE III : YES

CERCLA: NO

UN. NUMBER: UN 1950

RCRA: NO

DOT SHIPPING CLASS: ORM D 1950

TASCA INVENTORY : ALL INGREDIENTS LISTED

N.F.P.A. RATING: H-1,F-4,R-0

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF THIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR IT'S USE.

DATE PREPARED: 4/18/02

ZINC COLD GALVANIZING COMOUND,BRIGHT