



**ANTI-SEIZE TECHNOLOGY**  
A.S.T. Industries, Inc.

H.M.I.S.	
H -	2
F -	4
R -	0
P.P.	

# ZINC COLD GALVANIZING COMPOUND

STOCK # ('S): 17045

## MATERIAL SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTIFICATION

**MANUFACTURE:** ANTI-SEIZE TECHNOLOGY

2345 N. 17th. Ave.

FRANKLIN PARK, IL. 60131

**TELEPHONE #:** 847-455-2300

**24 HR. EMERGENCY #:** INFOTRAC @ 1-800-535-5053

### SECTION II - COMPOSITION

	CAS #	OSHA PEL,	TLV	SARA III,	PERCENT
ZINC	7440-66-6	5mg/m3	10mg/m3	YES	40 - 50
ALIPHATIC PETROLEUM DISTALLATES	8052-41-3	100ppm	100ppm	NO	1 - 10
METHYL ETHYL KETONE	78-93-3	200ppm	200 ppm	YES	10-20
XYLENE	1330-20-7	100ppm	100ppm	YES	5 - 15
ETHYLBENZENE ( COMPONENT OF XYLENE)	100-41-4	100 ppm	100ppm	YES	1 - 1.5
METHYL ISOBUTYL KETONE	108-10-1	50ppm	100ppm	YES	5 - 10
n-BUTYL ACETATE	123-86-4	150ppm	150ppm	NO	1 - 3
PROPANE / ISOBUTANE	74-98-6	1000ppm	1000ppm	NO	15- 25

### SECTION III - PHYSICAL PROPERTIES

**BOILING POINT:** - 40 - 310 F

**MELTING POINT:** DOES NOT APPLY

**VAPOR DENSITY ( AIR = 1):** HEAVIER THAN AIR

**EVAPORATION RATE (BUTYL ACETATE = 1):**SLOWER THAN ETHER

**APPEARANCE AND ODOR:** GRAY, SOLVENT ODOR, AEROSOL PRODUCT

**SOLUBILITY IN WATER:** SLIGHT

**REACTIVITY IN WATER:** NONE

**SPECIFIC GRAVITY:** 1.19

### SECTION IV - FIRE AND EXPLOSION DATA

**AEROSOL FLAMMABILITY:** - 156 F, EXTREMELY FLAMMABLE

**FLAMMABLE LIMITS:** LEL: 0.7 UEL: 15.0

**EXTINGUISHING MEDIA:** FOAM, CO2, DRY CHEMICAL

**SPECIAL FIRE FIGHTING PROCEDURES:** CANS MAY RUPTURE, BURST OR EXPLODE IN A FIRE. USE EXTREME CAUTION. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP. WEAR GOGGLES AND A SELF CONTAINED BREATHING APPARATUS.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** CANS MAY RUPTURE OR BURST, RELEASING THEIR CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

## SECTION V- PHYSICAL HAZARDS

**STABILITY:** (X) STABLE ( ) UNSTABLE

**CONDITIONS TO AVOID:** APPLICATION TO HOT SURFACES, STORAGE ABOVE 120F. EXPOSURE TO OPEN FLAMES.

**INCOMPARABILITY ,(MATERIALS TO AVOID):** STRONG OXIDIZING AGENTS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

## SECTION VI - HEALTH HAZARDS AND FIRST AID

**ROUTES OF ENTRY:**  SKIN  EYES  INHALATION  INGESTION

**HEALTH HAZARDS:** READ THE WARNING LABELS ON THE CAN FOR ADDITIONAL INFORMATION.

THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE HEALTH REACTION WHEN USED UNDER NORMAL CONDITIONS. THE SOLVENTS CONTAINED IN THIS PRODUCT HAVE BEEN KNOWN TO EFFECT THE CENTRAL NERVOUS SYSTEM IF THE CONCENTRATION IS HIGH ENOUGH. USE WITH ADEQUATE VENTILATION, LOCAL EXHAUST OR RESPIRATOR TO MAINTAIN THE AIR QUALITY. SYMPTOMS OF OVEREXPOSURE COULD INCLUDE DIZZINESS, HEADACHE, SKIN IRRITATION OR NARCOSIS.

### EMERGENCY FIRST AID PROCEDURES

**SKIN:** CONTACT MAY DRY THE SKIN. AVOID PROLONGED SKIN CONTACT. WASH WITH SOAP AND WATER, USING A NAIL BRUSH . PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

**EYES:** FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

**INGESTION:** NOT A LIKELY ROUTE OF EXPOSURE, DO NOT INDUCE VOMITING, . USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

**INHALATION:** THE SOLVENTS AND/OR PROPELLANTS IN THIS PRODUCT MAY EFFECT THE RESPIRATORY TRACT OR CENTRAL NERVOUS SYSTEM. AVOID OVEREXPOSURE. DIZZINESS OR RESPIRATORY IRRITATION ARE SIGNS OF OVEREXPOSURE. SEEK FRESH AIR. OR FOLLOW OTHER STANDARD MEDICAL PRACTICES..

**CHEMICAL ('S) LISTED AS CARCINOGENS ; ETHYLBENZENE , I.A.R.C. , POSSIBLE HUMAN CARCINOGEN**

**NPT ? : NO I.A.R.C. ? : YES OSHA ? : NO**

## SECTION VII - SPECIAL PRECAUTIONS AND SPILL PROCEDURES

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** STORE IN A COOL ,WELL VENTILATED AREA. DO NOT STORE ABOVE 120 F. .

**OTHER PRECAUTIONS:** DO NOT TAMPER WITH VALVE. DO NOT PUNCTURE, DO NOT SPAY IN EYES OR INGEST, READ THE PRODUCT LABEL FOR ADDITIONAL INFORMATION. KEEP AWAY FROM CHILDREN.

**SPILL/ LEAKAGE PROCEDURES:** AVOID BREATHING VAPORS. VENTILATE AREA AND REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN A CLOSE CONTAINER FOR DISPOSAL..

**WASTE DISPOSAL:** DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. REFER TO OTHER SECTIONS OF THIS MSDS FORM FOR ADDITIONAL INFORMATION

## SECTION VIII - SPECIAL PROTECTION INFORMATION

**RESPIRATORY PROTECTION:** NORMALLY NOT REQUIRED. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE A LOCAL EXHAUST TO REMOVE VAPORS, AND MAINTAIN AIR QUALITY. IF TLV'S ARE ABOVE ACCEPTABLE LIMITS USE A SELF CONTAINED BREATHING APPARATUS.

**PROTECTIVE GLOVES:** NORMALLY NOT REQUIRED

**EYE PROTECTION:** SAFETY GLASSES WITH SIDE SPLASH SHIELDS ARE RECOMMENDED.

**WORK/HYGIENIC PRACTICES:** USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

## SECTION X - REGULATORY INFORMATION

**CALIFORNIA PROPOSITION 65:** NO

**OZONE DEPLETING SUBSTANCES:** NO

**SARA TITLE III :**YES

**CERCLA:** YES

**UN. NUMBER:** UN 1950

**RCRA:** YES

**DOT SHIPPING CLASS:** ORM D 1950

**TASCA INVENTORY :** ALL INGREDIENTS LISTED

**N.F.P.A. RATING:** H-2,F-4,R-0

## SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF THIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR IT'S USE.

**DATE PREPARED:**4-18-2005

**Zinc Cold Galvanizing Compound..doc**