



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

H.M.I.S.	
H -	0
F -	3
R -	0
P.P.	A

FOOD MACHINERY GREASE AEROSOL, STOCK # ('S):17059 MATERIAL SAFETY DATA SHEET

Section 1- Chemical Product and Company Identification

Manufacture: Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131
Phone: 847-455-2300
Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053

Section 2-Composition/ Information on Ingredients

	CAS #	OSHA PEL,	TLV	SARA III	PROP 65,	PERCENT
HEXANE	110-54-3	50ppm	50ppm	NO	NO	30 -50
MINERAL SPIRITS	8052-41-3	100ppm	100ppm	NO	NO	1-10
GREASE MIXTURE	MIXTURE	NOT ESTABLISHED		NO	NO	40 - 60
PROPANE / ISOBUTANE	74-98-6	1000ppm	1000ppm	NO	NO	3 - 10

NOTE: MINERAL SPIRITS MAY CONTAIN AS MUCH AS 3.5% 1, 2, 4 TRIMETHYLBENZENE (CAS # 95-63-0) WHICH IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III

Section 3- Hazard Identification

ROUTES OF ENTRY: SKIN EYES INHALATION INGESTION

HEALTH HAZARDS: READ THE WARNING LABELS ON THE CAN FOR ADDITIONAL INFORMATION.

O VEREXPOSURE MAY CAUSE DIZZINESS OR NARCOSIS IN HIGH VAPOR CONCENTRATIONS. USE WITH ADEQUATE VENTILATION. DO NOT PURPOSEFULLY CONCENTRATE THE VAPORS. THE SOLVENTS CONTAINED IN THIS PRODUCT CAN CAUSE DEFATTING, OR IRRITATE THE SKIN IF PROLONGED SKIN CONTACT OCCURS.

CHRONIC EXPOSURE TO HIGH CONCENTRATIONS OF THESE SOLVENT VAPORS MAY CAUSE LUNG, LIVER OR KIDNEY DAMAGE. THE SOLVENTS CAN ALSO AFFECT THE CENTRAL NERVOUS SYSTEM. HEXANE HAS BEEN SHOWN TO DAMAGE PERIPHERAL NERVE TISSUE.

Section 4 – First Aid Measures

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH. PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES: FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION: NOT A LIKELY ROUTE OF EXPOSURE, **DO NOT INDUCE VOMITING.** USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION: THE SOLVENTS AND/OR PROPELLANTS IN THIS PRODUCT MAY AFFECT THE RESPIRATORY TRACT OR CENTRAL NERVOUS SYSTEM. AVOID OVEREXPOSURE. DIZZINESS OR RESPIRATORY IRRITATION ARE SIGNS OF OVEREXPOSURE. SEEK FRESH AIR. OR FOLLOW OTHER STANDARD MEDICAL PRACTICES.

CHEMICAL ('S) LISTED AS CARCINOGENS

NPT? NO I.A.R.C.? : NO OSHA? : NO

Section 5 – Fire Fighting Measures

FLASH POINT: -40 TO (NOT DETERMINE)

FLAMMABLE LIMITS: LEL: 1.8 UEL: 12.0

EXTINGUISHING MEDIA: FOAM, CO₂, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: CANS MAY RUPTURE, BURST OR EXPLODE IN A FIRE. USE EXTREME CAUTION. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP. WEAR GOGGLES AND A SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CANS MAY RUPTURE OR BURST, RELEASING THEIR CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD

Section 6 – Accidental Release Measures

SPILL/ LEAKAGE PROCEDURES: AVOID BREATHING VAPORS. VENTILATE AREA AND REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN A CLOSE CONTAINER FOR DISPOSAL.

Section 7 – Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL, WELL VENTILATED AREA. DO NOT STORE ABOVE 120 F.

OTHER PRECAUTIONS: DO NOT TAMPER WITH VALVE. DO NOT PUNCTURE, DO NOT SPAY IN EYES OR INGEST, READ THE PRODUCT LABEL FOR ADDITIONAL INFORMATION. KEEP AWAY FROM CHILDREN.

Section 8 – Exposure Controls / Personal Protection

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE A LOCAL EXHAUST TO REMOVE VAPORS, AND MAINTAIN AIR QUALITY. IF TLV'S ARE ABOVE ACCEPTABLE LIMITS USE A SELF CONTAINED BREATHING APPARATUS.

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED

EYE PROTECTION: SAFETY GLASSES WITH SIDE SPLASH SHIELDS ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

Section 9 – Physical and Chemical Properties

BOILING POINT: - 40 TO ND

MELTING POINT: DOES NOT APPLY

VAPOR DENSITY (AIR = 1): 4.0

EVAPORATION RATE (BUTYL ACETATE = 1): <1

APPEARANCE AND ODOR: WHITE SPRAY WITH SLIGHT SOLVENT ODOR

SOLUBILITY IN WATER: SOLUBLE

REACTIVITY IN WATER: NONE

SPECIFIC GRAVITY: 0.8

V.O.C. 'S: 25%

Section 10 – Stability and Reactivity

STABILITY: (X) STABLE () UNSTABLE

CONDITIONS TO AVOID: APPLICATION TO HOT SURFACES, STORAGE ABOVE 120F. AVOID EXPOSURE TO OPEN FLAMES.

INCOMPARABILITY, (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS, CHLORINE. DO NOT USE IN OXYGEN SYSTEMS.

HAZARDOUS DECOMPOSITION PRODUCTS: THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Section 11 – Toxicological Information

SEE SECTION 2 FOR ADDITIONAL INFORMATION AND EXPOSURE LIMITS

Section 12 – Ecological Information

NO ADDITIONAL INFORMATION IS AVAILABLE. THIS PRODUCT IS NOT EXPECTED TO BIOACCUMULATE.

Section 13 – Disposal Consideration

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDFILLED AT AN APPROVED FACILITY.

Section 14- Transport Information

SHIPMENT BY LAND: CONSUMER COMMODITY, ORM-D

SHIPMENT BY WATER: AEROSOL, 2, UN 1950, LTD QTY

SHIPMENT BY AIR: AEROSOL, 2, UN 1950, LTD QTY, PACKING INSTRUCTION Y203 APPLIES TO THESE SHIPMENTS

WHMIS: NOT REGULATED

HAZARD CLASS: COMBUSTIBLE, AEROSOL

Section 15 – Regulatory Information

CALIFORNIA PROPOSITION 65: NO

OZONE DEPLETING SUBSTANCES: NONE

SARA TITLE III: NO

CERCLA: NO

RCRA: NO

DOT SHIPPING CLASS: NOT HAZARDOUS

TASCA INVENTORY: ALL INGREDIENTS LISTED

N.F.P.A. RATING: H-1, F-4, R-0

Section 16 – Other Information:

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF HIS

PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR ITS USE.

DATE: 1/23/2009

Blank ANSI Style MATERIAL SAFETY DATA SHEET Form