



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

H.M.I.S.	
H -	1
F -	4
R -	0
P.P.	A

AST™ SILICONE LUBRICANT

INDUSTRIAL GRADE

STOCK # ('S): 17067

MATERIAL SAFETY DATA SHEET

Section 1- Chemical Product and Company Identification

Manufacture: Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131
Phone: 847-455-2300
Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053

Section 2-Composition/ Information on Ingredients

	CAS #	OSHA PEL,	TLV	SARA III	PROP 65,	PERCENT
HEXANE	110-54-3	500ppm	50ppm	NO	NO	40 -60
ISOBUTANE	75-28-5	1000ppm	1000ppm	NO	NO	15 - 30
SILICONE	63148-62-9	NOT ESTABLISHED				5 - 20

Section 3- Hazard Identification

ROUTES OF ENTRY: SKIN EYES INHALATION INGESTION

HEALTH HAZARDS: READ THE WARNING LABELS ON THE CAN FOR ADDITIONAL INFORMATION.

THIS PRODUCT IS NOT EXPECTED TO PRESENT A HEALTH HAZARD WITH NORMAL USE. THIS PRODUCT DOES CONTAIN SOLVENTS WHICH CAN EFFECT THE RESPIRATORY AND CENTRAL NERVOUS SYSTEM IF THE EXPOSURE IS HIGH ENOUGH. THE EFFECTS CAN INCLUDE DIZZINESS, HEADACHE, OR EYE IRRITATION. USE WITH ADEQUATE VENTILATION TO MAINTAIN AIR QUALITY.

Section 4 – First Aid Measures

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH. PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES: FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION: NOT A LIKELY ROUTE OF EXPOSURE, DO NOT INDUCE VOMITING. USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION: THE SOLVENTS AND/OR PROPELLANTS IN THIS PRODUCT MAY EFFECT THE RESPIRATORY TRACT OR CENTRAL NERVOUS SYSTEM. AVOID OVEREXPOSURE. DIZZINESS OR RESPIRATORY IRRITATION ARE SIGNS OF OVEREXPOSURE. SEEK FRESH AIR. OR FOLLOW OTHER STANDARD MEDICAL PRACTICES.

CHEMICAL ('S) LISTED AS CARCINOGENS

NPT? NO I.A.R.C. ? : NO OSHA? : NO

Section 5 – Fire Fighting Measures

AEROSOL FLAMMABILITY: EXTREMELY FLAMMABLE

FLAMMABLE LIMITS: LEL: 1.8 UEL: 12

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: CANS MAY RUPTURE, BURST OR EXPLODE IN A FIRE. USE EXTREME CAUTION. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP. WEAR GOGGLES AND A SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CANS MAY RUPTURE OR BURST, RELEASING THEIR CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

Section 6 – Accidental Release Measures

SPILL/ LEAKAGE PROCEDURES: AVOID BREATHING VAPORS. VENTILATE AREA AND REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN A CLOSE CONTAINER FOR DISPOSAL.

Section 7 – Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL, WELL VENTILATED AREA. DO NOT STORE ABOVE 120 F.
OTHER PRECAUTIONS: DO NOT TAMPER WITH VALVE. DO NOT PUNCTURE, DO NOT SPAY IN EYES OR INGEST, READ THE PRODUCT LABEL FOR ADDITIONAL INFORMATION. KEEP AWAY FROM CHILDREN.

Section 8 – Exposure Controls / Personal Protection

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE A LOCAL EXHAUST TO REMOVE VAPORS, AND MAINTAIN AIR QUALITY. IF TLV'S ARE ABOVE ACCEPTABLE LIMITS USE A SELF CONTAINED BREATHING APPARATUS.
PROTECTIVE GLOVES: NORMALLY NOT REQUIRED
EYE PROTECTION: SAFETY GLASSES WITH SIDE SPLASH SHIELDS ARE RECOMMENDED.
WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

Section 9 – Physical and Chemical Properties

BOILING POINT: -40 TO 156 F	SOLUBILITY IN WATER: NIL
MELTING POINT: DOES NOT APPLY	REACTIVITY IN WATER: NONE
VAPOR DENSITY (AIR = 1): 4.0	SPECIFIC GRAVITY: 0.6
EVAPORATION RATE (BUTYL ACETATE = 1): < 6	PERCENT VOLATILE: 94
APPEARANCE AND ODOR: CLEAR/ SOLVENT ODOR	

Section 10 – Stability and Reactivity

STABILITY: (X) STABLE () UNSTABLE
CONDITIONS TO AVOID: APPLICATION TO HOT SURFACES, STORAGE ABOVE 120F. EXPOSURE TO OPEN FLAMES.
INCOMPARABILITY, (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS: THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

Section 11 – Toxicological Information

SEE SECTION 2 FOR ADDITIONAL INFORMATION AND EXPOSURE LIMITS

Section 12 – Ecological Information

NO ADDITIONAL INFORMATION IS AVAILABLE. THIS PRODUCT IS NOT EXPECTED TO BIOACCUMULATE.

Section 13 – Disposal Consideration

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDFILLED AT AN APPROVED FACILITY.

Section 14- Transport Information

SHIPMENT BY LAND: CONSUMER COMMODITY, ORM-D

SHIPMENT BY WATER: AEROSOL, 2, UN 1950, LTD QTY

SHIPMENT BY AIR: AEROSOLS, FLAMMABLE, 2.1, UN 1950, LTD QT.
PACKAGING INSTRUCTION Y203 APPLIES TO THESE SHIPMENTS

Canadian WHMIS Classification: NOT REGULATED

Hazard Class: FLAMMABLE, AEROSOL

Section 15 – Regulatory Information

CALIFORNIA PROPOSITION 65: NO	RCRA: NO
OZONE DEPLETING SUBSTANCES: NONE	DOT SHIPPING CLASS: ORM-D, UN 1950
SARA TITLE III: NO	TASCA INVENTORY: ALL INGREDIENTS LISTED
CERCLA: NO	N.F.P.A. RATING: H-1, F-4, R-0

Section 16 – Other Information:

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF HIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR ITS USE.