



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

H.M.I.S.	
H -	1
F -	0
R -	0
P.P.	

AST-RTV™ SILICONE
ADHESIVE / SEALANT / INSTANT GASKET
8oz. PRESSURIZED CAN
STOCK # ('S): 27084,27085,27086,27087,27088,27089
MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURE: ANTI-SEIZE TECHNOLOGY
2345 N. 17th. Ave.
FRANKLIN PARK, IL. 60131

TELEPHONE #: 847-455-2300

24 Hr. EMERGENCY #: INFOTRAC@ 1-800-535-5053

SECTION II - COMPOSITION

	CAS #	OSHA PEL, TLV	SARA III	PROP 65,	PERCENT
METHYLTRIAACETOXSILANE	4253-34-3	NOT ESTABLISHED	NO	NO	1 - 5
ETHYLTRIAACETOXSILANE	17689-77-9	NOT ESTABLISHED	NO	NO	1-5
SILICA	7631-86-9	20mppcf 10mg/m3	NO	NO	10 - 20
NON-HAZARDOUS POLYMER	70131-67-8	NOT ESTABLISHED	NO	NO	70 - 90
NITROGEN	7727-37-9	NOT ESTABLISHED	NO	NO	

ACETIC ACID FUMES ARE FORMED DURING THE CURING PROCESS. THESE FUMES MAY BE IRRITATING TO THE RESPIRATORY TRACT. THE EXPOSURE LIMITS FOR ACETIC ACID IS 10ppm (PEL), 15ppm (STEL)

NOTE: THE OUTER COMPARTMENT CONTAINS A NON-FLAMMABLE PROPELLANT.

SECTION III - PHYSICAL PROPERTIES

BOILING POINT: DOES NOT APPLY	SOLUBILITY IN WATER: NIL
MELTING POINT: DOES NOT APPLY	REACTIVITY IN WATER: NONE
VAPOR DENSITY (AIR = 1): NO DATA	SPECIFIC GRAVITY: 1.04
EVAPORATION RATE (BUTYL ACETATE = 1): < 1	PERCENT VOLATILE: 3
APPEARANCE AND ODOR: VARIOUS COLOR'S SEALANT WITH SLIGHT VINEGAR LIKE ODOR	

SECTION IV - FIRE AND EXPLOSION DATA

AEROSOL FLAMMABILITY: PRODUCT IN NON-FLAMMABLE, OUTER COMPARTMENT CONTAINS NITROGEN WHICH IS NON FLAMMABLE BUT DOES NOT ESCAPE WHEN THE PRODUCT IS DISCHARGED.

FLAMMABLE LIMITS: LEL: NO DATA UEL: NO DATA

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: CANS MAY RUPTURE, BURST OR EXPLODE IN A FIRE. USE EXTREME CAUTION. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP. WEAR GOGGLES AND A SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CANS MAY RUPTURE OR BURST, RELEASING THEIR CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

SECTION V- PHYSICAL HAZARDS

STABILITY: (X) STABLE () UNSTABLE

CONDITIONS TO AVOID: APPLICATION TO HOT SURFACES, STORAGE ABOVE 120F. EXPOSURE TO OPEN FLAMES.

INCOMPARABILITY ,(MATERIALS TO AVOID):STRONG OXIDIZING AGENTS. WATER WILL CAUSE THE SEALANT TO CURE.

HAZARDOUS DECOMPOSITION PRODUCTS: ACETIC ACID VAPORS. THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARDS AND FIRST AID

ROUTES OF ENTRY: SKIN X EYES X INHALATION INGESTION

HEALTH HAZARDS: READ THE WARNING LABELS ON THE CAN FOR ADDITIONAL INFORMATION.

THIS PRODUCT RELEASES ACETIC ACID VAPORS WHEN THE PRODUCT IS CURING. THESE VAPORS MAY IRRITATE THE SKIN OR RESPIRATORY TRACT IF THE CONCENTRATION IS HIGH ENOUGH. THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE HEALTH REACTION UNDER NORMAL CONDITIONS OF USE. MAINTAIN THE AIR QUALITY BY USING WITH ADEQUATE VENTILATION, LOCAL EXHAUST OR RESPIRATOR. IF PROLONGED SKIN CONTACT IS EXPECTED, WEAR LATEX GLOVES TO MINIMIZE EXPOSURE.

EMERGENCY FIRST AID PROCEDURES

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH . PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES: FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION: NOT A LIKELY ROUTE OF EXPOSURE, DO NOT INDUCE VOMITING, . USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION: THE SOLVENTS AND/OR PROPELLANTS IN THIS PRODUCT MAY EFFECT THE RESPIRATORY TRACT OR CENTRAL NERVOUS SYSTEM. AVOID OVEREXPOSURE. DIZZINESS OR RESPIRATORY IRRITATION ARE SIGNS OF OVEREXPOSURE. SEEK FRESH AIR. OR FOLLOW OTHER STANDARD MEDICAL PRACTICES..

CHEMICAL ('S) LISTED AS CARCINOGENS

NPT ? : NO I.A.R.C. ? : NO OSHA ? : NO

SECTION VII - SPECIAL PRECAUTIONS AND SPILL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL ,WELL VENTILATED AREA. DO NOT STORE ABOVE 120 F. .

OTHER PRECAUTIONS: DO NOT TAMPER WITH VALVE. DO NOT PUNCTURE, DO NOT SPAY IN EYES OR INGEST, READ THE PRODUCT LABEL FOR ADDITIONAL INFORMATION. KEEP AWAY FROM CHILDREN.

SPILL/ LEAKAGE PROCEDURES: AVOID BREATHING VAPORS. VENTILATE AREA AND REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN A CLOSE CONTAINER FOR DISPOSAL..

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. REFER TO OTHER SECTIONS OF THIS MSDS FORM FOR ADDITIONAL INFORMATION

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE A LOCAL EXHAUST TO REMOVE VAPORS, AND MAINTAIN AIR QUALITY. IF TLV'S ARE ABOVE ACCEPTABLE LIMITS USE A SELF CONTAINED BREATHING APPARATUS.

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED . LATEX GLOVES IF PROLONGED SKIN CONTACT IS EXPECTED.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SPLASH SHIELDS ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

SECTION IX - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65: NO

OZONE DEPLETING SUBSTANCES: NONE

SARA TITLE III :

CERCLA: NO

UN. NUMBER: UN 1950

RCRA: NO

DOT SHIPPING CLASS: ORM-D, UN 1950

TASCA INVENTORY : ALL INGREDIENTS LISTED

N.F.P.A. RATING: H-1,F-1,R-0

SECTION X - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF THIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR IT'S USE.

DATE PREPARED 11/30/04

RTV SILICONE, 8oz PRESSURIZED CAN