



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

H.M.I.S.	
H -	0
F -	1
R -	0
P.P.	A

GRAPHITE / PETROLATUM

STOCK #: 47016

MATERIAL SAFETY DATA SHEET

Section 1- Chemical Product and Company Identification

Manufacture: Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131
Phone: 847-455-2300
Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 or 352-323-3500

Section 2-Composition/ Information on Ingredients

	CAS #	OSHA, PEL	OSHA TLV	302	355	372	%
PETROLATUM	8027-32-5	NO DATA	NO DATA	NO	NO		50
GRAPHITE	7440-44-0	2.5mg/m3	SAME	NO	NO		50

Section 3- Hazard Identification

ROUTES OF ENTRY: SKIN EYES INHALATION INGESTION
HEALTH HAZARDS: NONE REASONABLY FORESEEN.

Section 4 – First Aid Measures

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH. PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.
EYES: THIS PRODUCT COULD CAUSE SOME MECHANICAL IRRITATION IF GOTTEN INTO THE EYES AND RUBBED. FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.
INGESTION: IF INGESTED THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE REACTION. THIS PRODUCT CONTAINS PETROLEUM OIL; DO NOT INDUCE VOMITING, BECAUSE THE OIL MAY BE ASPIRATED INTO THE LUNGS. USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.
INHALATION: NOT LIKELY UNDER NORMAL CONDITIONS OF USE. IF USING IN HIGH TEMPERATURE APPLICATIONS WHERE THERMAL DECOMPOSITION IS LIKELY, USE A LOCAL EXHAUST TO REMOVE FUMES. IF DIZZINESS OR IRRITATION OCCURS, SEEK FRESH AIR.
CHEMICAL (‘S) LISTED AS CARCINOGENS: NONE
NPT? **I.A.R.C. ? :** **OSHA? :** _____

Section 5 – Fire Fighting Measures

FLASH POINT AND METHOD USED: > 350F, C.O.C.
FLAMMABLE LIMITS: LEL: NO DATA UEL: NO DATA
EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: THIS COMPOUND WILL NOT BURN UNLESS IT IS PRE-HEATED. WATER FOG MAY BE USED TO COOL THE CONTAINERS BUT DO NOT SPRAY DIRECTLY INTO LARGE CONTAINERS OF BURNING LIQUIDS AS FROTHING MAY OCCUR. WEAR A “N.I.O.S.H” APPROVED ORGANIC VAPOR RESPIRATOR.
UNUSUAL FIRE AND EXPLOSION HAZARDS: DENSE SMOKE AND NOXIOUS OR TOXIC FUMES MAY BE GENERATED IN A FIRE. FIRE FIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS.

Section 6 – Accidental Release Measures

SPILL/ LEAKAGE PROCEDURES: DUE TO THE VISCOUS NATURE OF THIS PRODUCT SPILL AND LEAKS ARE NOT EXPECTED. THIS MATERIAL CAN EASILY BE SCOOPED UP AND TRANSFERRED TO ANOTHER CONTAINER.

Section 7 – Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE AWAY FROM STRONG OXIDIZERS, EXTREME HEAT OR OPEN FLAMES. KEEP AWAY FROM CHILDREN
OTHER PRECAUTIONS: DO NOT TRANSFER TO UNMARKED CONTAINERS.

Section 8 – Exposure Controls / Personal Protection

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. IF THIS PRODUCT IS BEING USED IN HIGH TEMPERATURE APPLICATION WHERE THE PRODUCT "SMOKES" USE A LOCAL EXHAUST OR VENTILATE THE AREA TO MAINTAIN THE AIR QUALITY, OR USE A "N.I.O.S.H" APPROVED ORGANIC VAPOR RESPIRATOR. IF AN INDIVIDUAL IS REMOVING, DRY, FLAKY MATERIAL, USE A DUST RESPIRATOR.

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED. IF PROLONGED OR REPEATED SKIN CONTACT IS EXPECTED USE A LATEX GLOVE

EYE PROTECTION: SAFETY GLASSES ARE RECOMMENDED

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

Section 9 – Physical and Chemical Properties

BOILING POINT: >600F

MELTING POINT: 140F.

VAPOR PRESSURE: 1.0mmHg @20C

EVAPORATION RATE: 0

APPEARANCE AND ODOR: BLACK COLORED PASTE, NO SIGNIFICANT ODOR

SOLUBILITY IN WATER: NIL

REACTIVITY IN WATER: NONE

SPECIFIC GRAVITY: 1.1

PERCENT VOLATILE: 0

Section 10 – Stability and Reactivity

STABILITY: (X) STABLE () UNSTABLE

CONDITIONS TO AVOID: MAGNESIUM AND SOME OF ITS ALLOYS.

INCOMPATIBILITY: STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT UPON THE COMBUSTION CONDITIONS. NOXIOUS OR TOXIC FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Section 11 – Toxicological Information

SEE SECTION 2 FOR ADDITIONAL INFORMATION AND EXPOSURE LIMITS

Section 12 – Ecological Information

NO ADDITIONAL INFORMATION IS AVAILABLE. THIS PRODUCT IS NOT EXPECTED TO BIOACCUMULATE.

Section 13 – Disposal Consideration

WASTE DISPOSAL: DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDFILLED AT AN APPROVED FACILITY. THIS IS NOT A HAZARDOUS MATERIAL, IS NOT TOXIC AND IS NOT REGULATED UNDER ANY STATE OR FEDERAL GUIDELINES.

Section 14- Transport Information

SHIPMENT BY LAND: NOT REGULATED

SHIPMENT BY WATER: NOT REGULATED

SHIPMENT BY AIR: NOT REGULATED

WHMIS: NOT REGULATED

Section 15 – Regulatory Information

CALIFORNIA PROPOSITION 65: NO

OZONE DEPLETING SUBSTANCES: NONE

SARA TITLE III: NONE

CERCLA: NO

RCRA: NO

DOT SHIPPING CLASS: NOT HAZARDOUS

TASCA INVENTORY: ALL INGREDIENTS LISTED

NFPA RATING: H-1, F-2, R-0

Section 16 – Other Information:

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF HIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR ITS USE.

DATE: 1/21/2009

GRAPHITE PETROLATUM, 16 PART ISO MSDS