



www.antiseize.com

# SLICKON® GTS GOLD® Thread Sealant With PTFE®

## Product Description

**GTS GOLD** Engineered and tested to be FGG/BM/CZ® System Compatible with FlowGuard Gold®, Corzan® and BlazeMaster® pipe and fittings. General purpose use, paste consistency, heavy-duty, thread-sealing compound. Contains no solvents or other ingredients that harm CPVC plastics. Can be used on a many types of pipe including steel, brass, aluminum, stainless steel, copper, CPVC, PVC, ABS, Polyethylene, and Polypropylene.

## Features & Benefits

- Non-hardening, non-dripping, non-toxic
- Suitable for use with potable water
- Contains no solvents, non-curing
- Connections can be put into service immediately
- Self-lubricating
- Positive seal
- Brush-top applicator available

## Applications Include

Recommended for Pipes carrying Water, Steam, LP, Natural Gas, Refrigerants, Dilute Caustics, Acids, Diesel Fuel, Gasoline, Ethylene Glycol, Anti-Freeze and others.

## Temperature Range

-50°F to 500°F (-45° to 260°C)

Not suitable for use with oxygen or chlorine systems.

## Typical Properties

Property	Value
Consistency	Light paste, slightly granular
Color	Yellow
Specific Gravity	1.3
Temperature Range	-50° to 500°F (-45° to 260°C)
Pressure Range for Liquids	Up to 8,000 psi
Pressure Range for gases	Up to 2,000 psi
Service Time	There is NO drying time, maybe put into service immediately following assembly.
Shelf Life	2 years from the date of manufacture.

## Application Method

Clean all surfaces before application.

## Restrictions

Not for use on Oxygen Systems or Concentrated Chlorine.

## Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

### Available In:

1/2 pt bt	1 pt bt	1 qt can	1 qt bt	1 gal can	5 gal pail
54008	54018	54025	54026	54030	54050

*Slickon® is a registered trademark of Anti-Seize Technology.*

*FGG/BM/CZ® System Compatable indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, Corzan® and BlazeMaster® pipe and fittings.*

*FGG/BM/CZ®, FlowGuard Gold®, Corzan® and BlazeMaster® are registered trademarks of The Lubrizol Corporation.*