



www.antiseize.com

# RUST TREATMENT

## Product Description

**RUST TREATMENT** transforms rust into a dark, inert protective polymeric coating that seals out moisture and prevents future rust and corrosion. It also provides a superior primer coating on rusty steel and iron for the application of oil based paints.

\*\* Once painted, the surfaces resist the effects of weather without peeling and cracking.

\*\* Do not use with water based paints.

## Features & Benefits

- Stops rusting instantly
- Protects surfaces to resist the effects of weather
- Ready to use formula
- Eliminates lengthy surface preparations
- Acts as a Primer for oil based paints
- Does not leave a powdery surface
- Will not peel or crack
- Long-term protection on steel and iron
- Does not contain lead or phosphoric acid
- Non-flammable

## Applications include

- All rusting steel and iron
- Can be applied using a brush or roller
- Product arrives ready to use
- Read product label for additional application information

## Directions:

Complete directions are on the product label. Apply two coats allowing at least 20 minutes drying time between coats. Colder temperatures may take longer. Allow at least 48 hours cure time after final coat before applying an oil based paint.

Do not use in freezing conditions or temperatures over 100 F.

One gallon will cover 500 square feet of a smooth, non-porous surface. Irregular, porous surfaces will require more product. Spraying is not recommended. Do not dilute.

## Typical Properties

Property	Value
Color	Beige (in can), Black (after cured)
Flash Point	None °F
Specific Gravity	1.13 g/cm <sup>3</sup>
Weight Per Gallon	9.43 lb./gal
Toxicity	Not determined
Consistency	Viscosity: 1000 – 2000 cps
Shelf Life	1Year

## Cautions

Read all information on labels and Material Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use. See Warranty Statement in our Catalog or on our Website. Not suitable for use on non ferrous metals.

## Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

### Available In:

1 qt bottle w/sprayer	1 gal bottle	5 gal pail	55 gal drum
70000	70001	70005	70055

## **ANTI-SEIZE TECHNOLOGY**

2345 N. 17th AVE. • FRANKLIN PARK, IL 60131-3432  
847-455-2300 • [www.antiseize.com](http://www.antiseize.com)