THREAD SEALANTS

www.antiseize.com

TFE™

Pipe Thread Sealant w/PTFE

TFE™ is a non-hardening, heavy-duty pipe thread sealant. Thick-paste fortified with extra PTFE to give a positive seal with less effort. **TFE**™ contains no solvents, is non-toxic, non-staining, non-corrosive, non-dripping, self-lubricating, and applies to newly cut threads. UL Classified for gasoline, oil, gas, propane and sprinkler systems. NSF Registered. Withstands temperatures to 500°F (260°C) and pressures to 10,000 psi (liquid), 2,000 psi (gas).

Available In:	6oz tube	¼pt bt	½pt bt	1pt bt	1qt can	1gal can
P/N:	14008	14005	14012	14018	14025	14030

TUF-SET™

Blue HVAC Pipe Thread Sealant

Tuf-Set™ is specially designed for products commonly used in heating and Refrigeration, Commercial Plumbing, and Industrial applications. Fast drying, firm setting but stays flexible to resist vibration, provides excellent corrosion protection, non-toxic. Use with all metal pipe and most plastic pipe. Withstands temperatures -40° to 400°F (-40° - 204°C) and pressures up to 10,000 psi (liquid).

Available In:	¼pt bt	½pt bt	1pt bt	1qt can	1qt bt	1gal can
P/N:	56004	56008	56018	56025	56026	56030

SOF-SET™

Premium General Purpose Pipe Thread Sealant

Sof-Set™ is a semi-smooth thread-sealing compound. It is non-petroleum based with a high-solids content that firms up after application. Dries to a soft set, is corrosion inhibiting, non-seizing for disassembly, non-dripping, applies to newly cut threads, and withstands temperatures to 400°F (204°C) and pressures up to 10,000 psi (liquid), 2,600 psi (gas).

Available In:	½pt bt	1pt bt	1qt can	1qt bt	1gal can
P/N:	29010	29018	29025	29026	29030

SLICKON® GTS GOLD™

Thread Sealant w/PTFE

SLICKON® GTS GOLD™ is a general purpose thread-sealing compound engineered and tested to be compatible with CPVC pipe and fittings. Contains no solvents or other ingredients that harm CPVC plastics. Use on all kinds of piping. Withstands temperatures -50° to 500°F (-45°C to 260°C) and pressures up to 8,000 psi (liquid), 2,000 psi (gas).

Available In:	½pt bt	1pt bt	1qt can	1qt bt	1gal pail
P/N:	54008	54018	54025	54026	54030

S'MOOTH™

Thread Sealant With PTFE

S'MOOTH™ is a fast drying paste with a smooth consistency and no grit. A general-purpose metal pipe thread sealant, non-toxic, non-corrosive, resists dripping. Withstands temperatures -40° to 400°F (-40°C to 264°C), 450°F intermittent and pressures up to 5,000 psi. Has good chemical resistance.

Available In:	¼pt bt	½pt bt	1pt bt
P/N:	15005	15008	15018

AST-SEAL™ Std
AST-SEAL™ HD

Anaerobic Pipe Sealants w/PTFE

AST-SEAL™ **Std** (Standard Grade) is an excellent general-purpose pipe sealant with an instant permanent seal that cures in the absence of air. Withstands temperatures from -65º to 300ºF (-54º to 149ºC) continuous, 375ºF (191ºC) intermittent.

AST-SEAL™ **HD** (Heavy Duty) stainless steel grade is specifically made for stainless steel alloy fittings and is UL Classified. Heavy duty and faster curing than standard grade anaerobic. Withstands temperatures from -65º to 400ºF (-54º to 204ºC) continuous, 500ºF (260ºC) intermittent.

AST-SEAL Std and HD are not volatile or flammable, and prevent corrosion, seizing, galling, and vibration loosening. They seal pipes to 1,000 psi immediately after assembly, and up to the burst rating of a typical pipe after full cure.

Available In:	50ml tube	250ml tube	350ml bt	750ml can	10L pail
AST-SEAL Std P/N:	22050	22250	22350	22750	22010
AST-SEAL HD P/N:	22151	22152	22154	22153	22110

AST-SEAL™ HYD (Hydraulic)
AST-SEAL™ PH (Pneumatic/Hydraulic)

Anaerobic Thread Sealants

AST-SEAL™ **HYD** is a sealant for metal threads up to 1" diameter and can withstand hydraulic system pressures. It also exhibits high-temperature and solvent resistance to water and non-polar solvents.

AST-SEAL™ **PH** resists all hydraulic fluids and seals Pneumatic/Hydraulic systems. It is a thicker, non-running version of AST-SEAL™ HYD for overhead or inside machinery applications.

AST-SEAL™ **HYD and PH** offer non-destructive disassembly, non-shredding, non-contaminating, and are temperature resistant from -60° to 350°F (-51° to 176°C).

Available In:	10ml bottle	50ml bottle	250ml bottle
AST-SEAL HYD P/N:	22541	22542	22543
AST-SEAL PH P/N:	22544	22545	22546

AST-PPD™

Plumber's Pipe Dope Professional Grade



AST-PPD™ is a smooth, grit-free, pipe joint compound. It seals joints tight, will not crack or crumble, soft setting, non-hardening, and offers easy disassembly months or years later. Contains non-toxic inert oils and carbonate, no lead or silicone, and is safe for all water systems. Performs in temperatures with Gases and Liquid -15° to 400°F (-26° - 204°C), pressure range with Gases up to 1,000 psi, Liquids up to 2,000 psi, brushable to -15°F (-26°C)

Available In:	½pt bt	1pt bt	1qt can	1qt bt	1gal can
P/N:	25108	25118	25125	25126	25130

ANTI-SEIZE TECHNOLOGY
2345 N. 17TH AVE., FRANKLIN PARK, IL 60131
PHONE: 847-455-2300 • 1-877-ANTI-SEIZE • FAX: 847-455-2371
w w w . a n t i s e i z e . c o m

©2023 Anti-Seize Technology, Inc. All rights reserved.
SLICKON® is a registered trademark of Anti-Seize Technology, Inc.

SELLADORES

www.antiseize.com

TFE™

Sellador de Roscas de Cañería c/PTFE

TFE™ Sellador de roscas para tuberías de alta resistencia y no endurecido. Pasta espesa con PTFE adicional para dar un sello positivo con menos esfuerzo. El TFE™ no contiene disolventes, no es tóxico, no mancha, no es corrosivo, es autolubricante. Clasificado UL para sistemas de gasolina, petróleo, gas, propano y rociadores. Registrado por la NSF. Temperaturas a 500ºF (260ºC) y presiones a 10,000 psi (líquido), 2,000 psi (gas).

Disponibilidad:	6oz tube	¼pt bt	½pt bt	1pt bt	1qt can	1gal can
N/P:	14008	14005	14012	14018	14025	14030

TUF-SET™

Compuesto Azul Sellador para Rosca de Tubería HVAC

Tuf-Set™ está especialmente diseñado para productos utilizados para calefacción y refrigeratión, piomería commercial y aplicaciones industriales. De secado rápido, forma una capa firme pero flexible para resistir vibraciones. Provee una excelente protección para la corrosion y es no tóxico. Puede utilizarse con todo tipo de tubo metálico y con practicamente todos los tubos plásticos. Resiste temperaturas de hasta -40° a 400°F (-40° a 204°C) y presiones de hasta 10.000 lppc (liquido).

Disponibilidad:	¼pt bt	½pt bt	1pt bt	1qt can	1qt bt	1gal can
N/P:	56004	56008	56018	56025	56026	56030

SOF-SET™

Sellador Premium para Rosca de Tubería de Propósito Generala

Sof-Set™ es un compuesto de sellado para roscas semiliso. No está hecho base de petróleo, con contenido alto en sólidos que se endurece luego de la aplicación. Se seca formando una capa sin tensión. Inhibe la corrosión, sin agarrotamiento para el desmontaje, no gotea, se aplica a roscas recientemente cortadas, y resiste temperaturas de hasta 400°F (204°C) y presiones de hasta 10.000 lppc (liquido), 2,600 lppc (gas).

Disponibilidad:	½pt bt	1pt bt	1qt can	1qt bt	1gal can
N/P:	29010	29018	29025	29026	29030

SLICKON® GTS GOLD™

Sellador para Roscas c/PTFE

SLICKON® GTS GOLD™ es un compuesto sellador de roscas de uso general diseñado y probado para ser compatible con tuberías y accesorios de CPVC. No contiene solvents ni ingredientes que dañen plásticos CPVC. Se puede usar en todo tipo de tubería. No utilizer en cloro concentrado. Resiste temperatureas de hasta -50° a 500°F (-45° a 260°C) y presiones de hasta 8.000 lppc (liquido), 2.000 lppc (gas).

Disponibilidad:	½pt bt	1pt bt	1qt can	1qt bt	1gal pail
N/P:	54008	54018	54025	54026	54030

S'MOOTH™

Sellador para roscas c/PTFE

S'MOOTH™ es una pasta de secado rápido con una consistencia lisa y sin particulas. Sellador para roscas de tuberías metálicas de propósito general, no tóxico, no corrosive, y que resiste el goteo. Resiste temperaturas de hasta -40° a 400°F (-40° a 204°C) intermittent y presiones al lppc 5.000. Buena resistencia quimica.

Disponibilidad:	¼pt bt	½pt bt	1pt bt
N/P:	15005	15008	15018

AST-SEAL™ Std
AST-SEAL™ HD

Selladores de Tubos Anaeróbicos c/PTFE

AST-SEAL™ **Std** (Grado estándar) es un excelente sellador de tubos de propósito general con un sello instantáneo permanente que cura en ausencia de aire. Resiste temperaturas desde -65° a 300°F (-54° a 149°C) en forma continua, y de 375°F (191°C) en forma intermitente.

AST-SEAL™ **HD** (muy resistente) de grado de acero inoxidable está especialmente pensado para adaptadores de aleaciones de acero inoxidable y está clasificado por UL. Muy resistente y de curación más rápida que los anaeróbicos de grado estándar. Resiste temperaturas desde -65° a 400°F (-54° a 204°C) en forma continua y de 500°F (260°C) en forma intermitente.

AST-SEAL Std y HD no son volátiles ni inflamables, evitan la corrosión, el agarrotamiento, el ludimiento y el afloje por vibración. Sellan tubos de hasta 1.000 lppc inmediatamente después de la asamblea, y hasta la maxima capacidad para incrementos repentinos de un tubo tipico después de totalmente seco.

Disponibilidad:	50ml tube	250ml tube	350ml bt	750ml can	10L pail
AST-SEAL Std N/P:	22050	22250	22350	22750	22010
AST-SEAL HD N/P:	22151	22152	22154	22153	22110

AST-SEAL™ HYD (Hidráulico)
AST-SEAL™ PH (Neumático / Hidráulico)

Selladores de Roscas Anaeróbicos

AST-SEAL™ **HYD** es un sellador para roscas metálicas con un diámentro de hasta l pulgada y que puede resistir presiones de sistemas hidráulicos. También demustra resistencia a solvents, altas temperaturas, al aqua y solvents no polares.

AST-SEAL™ **PH** resiste todaos los fluidos hidráulicos y sella sistemas neumáticos/hidráulicos. Es una version más gruesa y que no se corre del AST-SEAL HYD para aplicaciones aéreasd o aplicaciones dentro de la máquina.

AST-SEAL™ **HYD y PH** permiten un desmontaje no destructivo, no triturante. No contaminan y resisten temperaturas desde -60° a 350°F (-51° a 176°C).

Disponibilidad:	10ml bottle	50ml bottle	250ml bottle
AST-SEAL HYD N/P:	22541	22542	22543
AST-SEAL PH N/P:	22544	22545	22546

AST-PPD™

Pasta para Plomeria Grado Profesional



AST-PPD™ es un compuesto para junta de tubos liso sin particulas. Sella fuertemente las juntas, capa sin tension, no se endurece, no se fracturará ni desmenuzará, y permitirá un desmontaje sencillo meses o años más tarde. Contiene carbonato y aceites intertes no tóxicos, sin plomo no silicona y es seguro para todos los sistemas de agua. Resiste temperaturas de hasta Gases y liquidos - 15° a 400°F (-26° a 204°C), y presiones de hasta Gases hasta 1.000 lppc; liquidos hasta 2.000 lppc, pincelable -15°F (-26°C).

Disponibilidad:	½pt bt	1pt bt	1qt can	1qt bt	1gal can
N/P:	25108	25118	25125	25126	25130

ANTI-SEIZE TECHNOLOGY
2345 N. 17TH AVE., FRANKLIN PARK, IL 60131
PHONE: 847-455-2300 • 1-877-ANTI-SEIZE • FAX: 847-455-2371
www.antiseize.com

©2023 Anti-Seize Technology, Inc. Todos los derechos reservados.
SLICKON® es marca registrada de Anti-Seize Technology, Inc.