



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

CHAIN AND CABLE LUBE

SAFETY DATA SHEET

Section 1- Product and Company Identification

Product Code: 17040

Manufacture/Supplier : Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131

Phone: 847-455-2300

Fax: 847-455-2371

Web: antiseize.com

Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 (US & Canada)
1-352-323-3500 (International)

Web: infotrac.net

Product Use: cable lubricant and rust inhibitor

Date: January, 20, 2021

Section 2-Hazard Identification

GHS Classification (Hazcom 2012):

Physical

Flammable Aerosol Category 1

Contains gas under pressure: may explode if heated-Pressurized gas

STOT SE3-May cause respiratory irritation

STOT RE2- May cause damage to organs through prolonged or repeated exposure

Label Elements:



Signal word:

Danger

Hazard Statement:

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

May cause respiratory irritation

Causes damage to organs through prolonged or repeated exposure

Precautionary Phrases:

Keep away from heat/sparks/open flames/hot surfaces-no smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Do not breathe dust/fumes/gas/mist/vapors/spray
Use only outdoors or in a well ventilated area

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage:

Protect from sunlight.
Do not expose to temperatures exceeding 50°C /122°F
Store locked up

Disposal: Dispose of container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations

Section 3- Composition/ Information on Ingredients

This product is a mixture of the substances listed below with nonhazardous additions which are not hazardous and not listed

CHEMICAL	CAS NUMBER	PERCENT
Mineral Spirits	64742-47-8	5-10
Propane	74-98-6	5-10
n-Butane	106-97-8	5-10

The specific identity and/or exact percentage of composition has been withheld as a trade secret

Section 4 – First Aid Measures

Eye: Immediately flush eyes with water. Remove contact lenses if present and easy to do, continue rinsing, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: In case of contact, wash thoroughly with plenty of soap and water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: Not a likely source of exposure. Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention.

Most Important symptoms and effects, both acute and delayed: May cause eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention required for ingestion.

Section 5 – Fire Fighting Measures

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Extremely flammable aerosol. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans. Water fog nozzle is preferred.

Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

Section 7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not smoke while using.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

Section 8 – Exposure Controls / Personal Protection

CHEMICAL NAME	EXPOSURE LIMITS
Mineral oil	5mg/m ³ , mist, PEL OSHA , Long term value 10mg/m ³ , mist REL OSHA short term value
Propane	1000ppm TWA OSHA 1800mg/m ³ PEL OSHA 1000rel NIOSH
Butane	1900mg/m ³ OSHA PEL 1000ppm OSHA REL

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

Individual Protection Measures: Remove contaminated clothing. Wash hands after use.

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin Protection: Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

Section 9 – Physical and Chemical Properties

Appearance: Aerosol product,	Vapor Density (air = 1): heavier than air
-------------------------------------	--

Odor: mild	Specific Gravity: 0.8
Odor Threshold: Not established	Water Solubility: Not determined
pH: Not available	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: No Data	Autoignition Temperature: Not available
Boiling Point: -48°F, (-44°C)	Decomposition Temperature: Not available
Flash Point: -2.2°F, (-19°C)	Viscosity: Not available
Evaporation Rate: slower than ether	Explosion Properties: None
Flammable Limits: LEL: estimated 9.5% (V) UEL: estimated 2.2% (V)	Oxidizing Properties: Not oxidizing
Vapor Pressure: Not established	Aerosol Fire Protection Level: Level 2 Aerosol (NFPA 30B)
VOC Content: 24.8 %	Flammability (solid, gas): gas, level 3 Aerosol

Section 10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Use with strong oxidizing chemicals such as concentrated acids.

Incompatible Materials: Avoid strong oxidizing agents and acids.

Hazardous Decomposition Products: The thermal decomposition products are highly dependent upon the combustion conditions. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

Section 11 – Toxicological Information

Long term Toxicological studies have not been conducted for this product.

Potential Health Effects:

Eye: May cause mild irritation.

Skin: Prolonged contact may cause mild irritation of the skin.

Inhalation: No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation .

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea

Chronic Hazards: Prolonged inhalation of thermal decomposition products may result in lung damage.

Carcinogen Status: None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

Section 12 – Ecological Information

Long term ecological studies have not been conducted for this product

Aquatic Toxicity: Hazardous for water, do not empty into drains

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes

Other information: This product does not contain

Section 13 – Disposal Consideration

Waste disposal: Dispose of in a responsible manner. Follow local, state and federal guidelines. Do not discharge into sewers or waterways. Incineration is the preferred method of disposal, although it may be landfilled at an approved facility.

Section 14- Transport Information

DOT Proper Shipping Name: UN1950, Aerosols, 2.1, Limited Quantity

DOT Technical Name: None

DOT Hazard Class: 2.1

UN Number: UN1950

DOT Labels Required (49CFR172.101): LTD QTY

IMDG Proper Shipping Name: Aerosols, Limited Quantity,

ID Number: UN1950

Hazard Class: 2.1

Packing Group: None

Labels Required: None

Marking Required: Limited Quantity Mark

ICAO/IATA

Proper shipping name: Aerosol, Flammable

Hazard Class: 2.1

Identification Number: UN 1950

Packing Group: None

Section 15 – Regulatory Information

Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ:

Propane 100lb RQ

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

EPA TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: No ingredients are listed

Section 16 – Other Information:

The information contained herein is based on data considered accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of his product. Therefore, because the product may be used under conditions beyond our control, we assume no liability for its use.