

COOL-CUT™

SAFETY DATA SHEET

Section 1- Product and Company Identification

Product code: 17050

Manufacture/Supplier : Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131

Phone: 847-455-2300

Fax: 847-455-2371

Web: antiseize.com

Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 (US & Canada)

1-352-323-3500 (International)

Web: infotrac.net

Product Use: Safety Solvent and Degreaser

Restriction of Use: Use only as directed

Date: April 30, 2019

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification (Hazcom 2012):

Carcinogenicity – Category 2

Eye irritation – Category 2

Gases under pressure- Dissolved Gas

Skin Sensitizer – Category 2

Skin Sensitizer– Category 1B

Specific Target Organ Toxicity – Single Exposure (Narcotic Effect) Category 3

Label Elements:



Signal word:

WARNING

Hazard Phrases – Physical:

Contains gas under pressure: May explode if heated

Hazard Statements- Health

Suspected of causing Cancer

Causes serious eye irritation

Causes skin irritation

May cause an allergic skin reaction
May cause drowsiness or dizziness

Precautionary Phrases – General:

If medical advice is needed, have product container or label at hand
Keep out of reach of children.
Read label before use.

Precautionary Phrases – Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing fume/ gas/ mist / vapors/ spray.
In case of inadequate ventilation wear respiratory protection.
Wash thoroughly after handling.
Wear protective gloves/ eye protection.
Avoid breathing vapors or spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in well ventilated area

Precautionary Phrases – Response:

IF exposed or concerned: Get medical attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing
If eye irritation persists: Get medical advice/ attention.
IF ON SKIN: wash with soap and water.
Take off contaminated clothing and wash it before reuse .
If skin irritation or a rash occurs : Get medical attention
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell.

Precautionary Phrases – Storage:

Store locked up
Protect from sunlight
Store in well ventilated place

Precautionary Phrases – Disposal:

Dispose of contents/ container according to local, state, national and international regulations.

Section 3- Composition/ Information on Ingredients

CHEMICAL	CAS NUMBER	PERCENT
Tetrachloroethylene	127-18-4	90-100
Carbon Dioxide	124-38-9	5-10

The specific identity and/or exact percentage of composition has been withheld as a trade secret.

Section 4 – First Aid Measures

Eye: Flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: Remove all contaminated clothing and wash thoroughly before reuse. Wash thoroughly with plenty of water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: If swallowed contact physician or poison control center. Rinse mouth.

Most Important symptoms and effects, both acute and delayed: May cause drowsiness and dizziness, Headache, Nausea, vomiting. Irritation of eyes and mucus membranes. Irritation of nose and throat. Skin Irritation. May cause redness and pain. Causes damage to the Central Nervous System, Liver, Kidney, Respiratory system through prolonged or repeated exposure. May cause cancer.

Indication of any immediate medical attention and special treatment needed: Narcosis. Treat symptomatically. Keep victim under observation. Provide supportive measures. Remove to fresh air.

Section 5 – Fire Fighting Measures

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical. DO NOT use water jet as an extinguisher, this will spread the fire.

Special Hazards Arising from the Chemical: Contents under pressure, exposure to high temperatures may cause containers to burst. Water fog may be used to cool the containers but do not spray directly into large containers of burning liquids as frothing may occur. Dense smoke and noxious or toxic fumes may be generated in a fire. The thermal decomposition products are highly dependent upon the combustion conditions. Vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

Section 6 – Accidental Release Measures

Emergency Procedure:

Keep, unnecessary people away; isolate hazard area and deny entry. Wear appropriate equipment and clothing during cleanup. Do not touch or walk through spilled material. Avoid breathing mist or vapor. Wear a NIOSH approved respirator if necessary. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for proper disposal. Keep area well ventilated.

Recommended Equipment:

Positive pressure, full-face piece self contained breathing apparatus (SCUBA), or positive pressure supplied air respirator with escape SCUBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Wear a NIOSH Organic Vapor respirator or SCUBA gear for larger spills. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing and protective gloves.

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment, such as protective gloves, protective clothing and a NIOSH approved Organic Vapor respirator. Use caution: slip hazard.

Environmental Hazards:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other

unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Collect liquid spill with an inert absorbent material and place into a suitable container for disposal. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or entering sewers or drainage system that lead to waterways.

Section 7 – Handling and Storage

General:

- For industrial use only.
- Do not use before reading instructions.
- Pressurized container, do not pierce or burn.
- Do not spray on naked flames or any other incandescent material.
- Open doors or windows while using product and product is drying to keep ventilation adequate.
- Do not cut, weld, solder, drill, grind or expose container to heat.
- Contents under pressure: Do not expose to heat or store at temperatures above 50°C / 122°F.
- For used by trained personnel only.
- Keep away from children.
- Wash hands after use.
- Do not get in eyes, on skin or on clothing.
- Do not breathe vapors or mists.
- Avoid release to the environment, do not pour down drains.
- Use good personal hygiene practices.
- Eating, drinking and smoking in work areas is prohibited.
- Remove contaminated clothing and protective equipment.
- Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Keep windows and doors open while product is in use and drying or use a NIOSH Organic vapor respirator to keep exposure levels below recommended guidelines.

Storage Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated areas away from heat, or open flames. If exposed to high temperatures the container may burst. Protect against physical damage. Empty container retain residue and may be dangerous.

Do not cut, drill, grind, weld or perform similar operations on or near containers.
Store at temperatures below 120°F.

Section 8 – Exposure Controls / Personal Protection

CHEMICAL NAME	EXPOSURE LIMITS
CARBON DIOXIDE	5,000 ppm OSHA PEL 30,000 ppm ACGIH STEL 30,000 ppm NIOSH TWA
Tetrachloroethylene	100 ppm OSHA TWA 25 ppm ACGIH TWA

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. Local exhaust ventilation may be required. Ventilation that includes 10 air changes per hour should be used.

Individual Protection Measures:

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice. In confined spaces and emergency situations use a self contained breathing apparatus. Air monitoring is needed to determine actual employee exposure levels.

Skin Protection: Impervious gloves such as rubber or Nitrile recommended where needed to avoid prolonged skin contact. Chemical resistant clothing is also recommended to avoid prolonged contact. Avoid unnecessary skin contact.

Eye Protection: Safety glasses with splash shields or goggles recommended where needed to avoid eye contact.

Section 9 – Physical and Chemical Properties

Appearance: Colorless	Vapor Density (air = 1): 5.7
Odor: Irritating	Specific Gravity: 1.6
Odor Threshold: 50 ppm	Water Solubility: 0.02% (77°F / 25°C)
pH: Not available	Octanol/Water Partition Coefficient: 2.88
Melting Point/Freezing Point: -8.1°F (-22.3°C) estimated	Autoignition Temperature: Not available
Boiling Point: 250.3°F (121.3 °C) estimated	Decomposition Temperature: Not available
Flash Point: None (Tag Closed Cap)	Viscosity: Not available
Evaporation Rate: Very Fast	Explosion Properties: None
Flammable Limits: LEL: N/A UEL: N/A	Oxidizing Properties: Not oxidizing
Vapor Pressure: 18.47 mmHg@25C	Aerosol Fire Protection Level: Not applicable
VOC Content: 0	Flammability (solid, gas): Not flammable

Section 10 – Stability and Reactivity
--

Stability: Stable under normal conditions of use, storage and transport.

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known under normal condition of use.

Conditions to Avoid: High temperatures.

Incompatible Materials: Styrene

Hazardous Decomposition Products: Hazardous decomposition products may include carbon dioxide, carbon monoxide and other toxic fumes.

Section 11 – Toxicological Information

Potential Health Effects:

Eye: May cause mild irritation.

Skin Corrosion /Irritation: Prolonged contact may cause mild irritation of the skin.

Inhalation: Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache, nausea and vomiting.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Chronic Hazards: Suspect cancer hazard. Overexposure may cause kidney damage. May cause liver disorders (e.g. edema, porteinuria) and damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin or eyes.

Carcinogen Status: IARC, Tetrachloroethylene, 2A Probable carcinogenic to humans.
NTP: Reasonably anticipated to be a human carcinogen.

Aspiration Hazards: Hazardous if swallowed, may be fatal is swallowed and enters airways.

Acute Toxicity: Inhalation: effect of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death. Narcotic effects.

Germ Cell Mutagenicity: No data available to indicate product or any components at greater than 0.1% are mutagenic or genotoxic.

Tetrachloroethylene

Acute

Dermal,LD50,Rabbit, 3305 mg/kg estimated

Inhalation ,LC50, Rat, 20 mg/l, 4 hours estimated

Oral, LD50 , Rat , 2691. mg/kg estimated

Section 12 – Ecological Information

Tetrachloroethylene

Ecotoxicity:

Fish, LC50, 19 mg/l, 96 hours estimated

Components:

Tetrachloroethylene

Fish LC50, Rainbow trout, Donaldson trout 4.7-5.2 mg/l, 96 hours

Bioaccumulative Potential: Not available.

Partition coefficient n-octanol / water (log Kow)
Tetrachloroethylene **2.88**

Persistence and Degradability: Not available.

Mobility in Soil: Not available.

Other Adverse Effects: No Data

Section 13 – Disposal Consideration

Waste disposal: This material and its container must be disposed of as a hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers, Water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code:

D039: Waste Tetrachloroethylene

F001: Waste Halogenated Solvent – Spent Halogenated Solvent used in Degreasing

F002: Waste Halogenated Solvent – Spent Halogenated Solvent

US RCRA Hazardous Waste U list: Reference

Tetrachloroethylene (CAS 127-18-4) U210

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14- Transport Information

DOT

UN number: UN1950

UN proper shipping name Aerosols, Non-Flammable (each not exceeding 1 L capacity) (LTD-QTY)

Transport Hazard Classes

Class 2.2,
Labels LTD QTY

IATA

UN number: UN1950

UN proper shipping name Aerosols, non flammable,(each not exceeding 1 L capacity) (LTD-QTY)

Transport Hazard Classes:

Class 2.2 LTD QTY
Subsidiary Risk 6.1

Other information

**Passenger aircraft
and cargo aircraft** Forbidden
Cargo aircraft only Forbidden

IMDG

UN Number UN 1950

UN proper shipping name AEROSOLS

Transport hazard classes

Class 2.2, LTD QTY

Section 15 – Regulatory Information

US federal regulations This product is a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

TSCA Section 12 (b) Export Notification (40 CFR 707, Subpt. D)
Not regulated

SARA 304 Emergency Release Notification
Not required

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed

US EPCRA (SARA Title III) Section 313 – Toxic Chemical: Listed Substance
Tetrachloroethylene (CAS 127-18-4)

CERCLA Hazardous Substances : Reportable Quantity
Tetrachloroethylene (CAS 127-18-4) 100 LBS
Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your local emergency planning committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Tetrachloroethylene (CAS 127-18-4)


Clean Air Act (CAA) Section 112 (r) Accidental Release Prevention (40 CFR 68.130)
Not regulated

Safe Water Drinking Act (SDWA)
Not Regulated

Food and Drug Administration (FDA)
Not Regulated

Superfund Amendments and Reauthorization Act of 1986 (SARA)
Section 311/312 Hazard Categories Immediate Hazard – Yes
Delayed Hazard – Yes
Fire Hazard – No
Pressure Hazard – Yes
Reactivity Hazard – No

SARA 302 Extremely Hazardous Substance
No

U.S. California Proposition 65:  **WARNING:** This product can expose you to Tetrachloroethylene which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

Section 16 – Other Information:

Notice to reader:

The information contained herein is based on data considered accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of his product. Therefore, because the product may be used under conditions beyond our control, we assume no liability for its use.