



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

SLICKON[®] FLOW-LUBE[™]

SAFETY DATA SHEET

Section 1- Product and Company Identification

Product Code: 17064

Manufacture/Supplier : Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131

Phone: 847-455-2300

Fax: 847-455-2371

Web: antiseize.com

Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 (US & Canada)
1-352-323-3500 (International)

Web: infotrac.net

Product Use: General Lubrication

Date: March 11, 2022

Section 2-Hazard Identification

GHS Classification (Hazcom 2012):

Skin corrosion/irritation, Category 2
STOT, Single exposure, Category 3
Aspiration Toxicity, Category 1
Flammable Aerosol, Category 1
Gases under pressure- Compressed gas

Label Elements:



Signal word:

Danger

Hazard Phrases:

Causes skin irritation
May cause respiratory irritation.
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways.
May be harmful if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated

Precautionary Phrases:**Prevention:**

Wash hands and face thoroughly after handling
Wear protective gloves
Avoid breathing fume/gas/mist/vapors/spray
Use only outdoors or in well ventilated area
Keep away from heat/sparks/open flames/hot surfaces – No smoking
Do not spray on an open flame or other ignition sources
Pressurized container; Do not pierce or burn, even after use

Response:

IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice, attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do **NOT** induce vomiting.

Storage:

Store locked up
Store in well ventilated place.
Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F

Disposal: Dispose of contents in accordance with local, regional and national regulations.

Section 3- Composition/ Information on Ingredients

CHEMICAL	CAS NUMBER	PERCENT
Distillates(petroleum)Hydrotreated light distillates	64742-47-8	20-30
Petroleum oil	64742-52-5	20-30
Propane/isobutane/n-butane	68476-86-8	10-20
Petroleum oil	64742-62-7	10-20
Naphthenic oil, severely hydrotreated	64742-52-5	1-10
Dipropylene Glycol Mono Methyl Ether	34590-94-8	1-10
Ethyl Acetic Ester	141-78-6	1-10
Polytetrafluoroethylene	9002-84-0	0.1-1.0

The specific identity and/or exact percentage of composition has been withheld as a trade secret

Section 4 – First Aid Measures

General: Avoid contact with eyes, skin and clothing. Avoid breathing vapors, mist and gas.

Eye: Immediately flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: In case of contact, wash thoroughly with plenty of soap water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If breathing has stopped contact emergency medical services immediately and start artificial respiration. If symptoms persist call a physician or seek medical care.

Ingestion: Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious or semiconscious person. Risk of product entering airway on vomiting after ingestion. Call a physician or Poison Control Center immediately.

Most Important symptoms and effects, both acute and delayed: Causes eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention required for ingestion.

Section 5 – Fire Fighting Measures

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Extremely flammable aerosol. Keep away from heat and open flames. Do not spray onto hot surfaces. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area. The material can be soaked up using appropriate materials for oil based products. Dispose of absorbent properly.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

Section 7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not tamper with valve. Do not spray onto hot surfaces. Do not smoke while using.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

Section 8 – Exposure Controls / Personal Protection

CHEMICAL NAME	EXPOSURE LIMITS
Hydrotreated light distillates	200ppm ACGIH TLV, 8 hr
Petroleum oil	5mg/m ³ OSHA PEL (as mist)

Propane/isobutane/n butane	1000ppm ACGIH TLV 1000ppm OSHA PEL TWA
Petroleum oil	5mg/m3 OSHA PEL (as mist)
Naphthenic oil, severely hydrotreated	5mg/m3 OSHA PEL (as mist)
Dipropylene Glycol Mono Methyl Ether	100ppm ACGIH TWA 100 ppm OSHA PEL
Ethyl Acetic Ester	400ppm ACGIH TLV 400ppm OSHA PEL

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

Individual Protection Measures:

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin Protection: Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

Section 9 – Physical and Chemical Properties

Appearance: Amber colored aerosol liquid	Vapor Density (air = 1): Not Available
Odor: slight petroleum odor	Specific Gravity: 0.8
Odor Threshold: Not established	Water Solubility: Not soluble
pH: Not available	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: Not available	Autoignition Temperature: Not available
Boiling Point: Not available	Decomposition Temperature: Not available
Flash Point: -156°F, -104°C (for propellant)	Viscosity: Not available
Evaporation Rate: slower than ether	Explosion Properties: None
Flammable Limits: LEL: Not established UEL: Not established	Oxidizing Properties: Not oxidizing
Vapor Pressure: Not established	Aerosol Fire Protection Level: Not available
VOC Content: 22.7 MIR Value: 0.38	Flammability (solid, gas): gas

Section 10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Use with strong oxidizing chemicals such as concentrated acids.

Incompatible Materials: Avoid strong oxidizing agents and acids.

Hazardous Decomposition Products: The thermal decomposition products are highly dependent upon the combustion conditions. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

Section 11 – Toxicological Information

Long term Toxicological studies have not been conducted for this product

Potential Health Effects:

Eye: May cause mild irritation.

Skin: Prolonged contact may cause mild irritation of the skin.

Inhalation: No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation .

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea

Chronic Hazards: Prolonged inhalation of thermal decomposition products may result in lung damage.

Carcinogen Status: None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

Chemical Name	LD50 oral	LD50 Dermal	LC50 inhalation
Hydrotreated light distillates	>5,000mg/kg (Rat)	>2,000mg/kg (Rabbit)	>5.2mg/L (Rat) 4 hr.
Petroleum oil	>5,000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	=2.18 mg/L (Rat) 4 hr
Propane/isobutane/n butane	-	-	=31mg/L (Rat) 4 hr.
Naphthenic oil, severely hydrotreated	>5,000mg/kg (Rat)	>2,000mg/kg (Rabbit)	>5.2mg/L (Rat) 4 hr.
Dipropylene Glycol Mono Methyl Ether	=5400 uL/kg (Rat)	=9500 mg/kg (Rabbit)	-
Ethyl Acetic Ester	=5620 mg/kg (Rat)	18000 mg/kg (Rabbit)	-

Section 12 – Ecological Information

Long term ecological studies have not been conducted for this product

Ecotoxicity: No Data

Bioaccumulative Potential: No Data

Mobility in Soil: No Data

Other Adverse Effects: No Data

Section 13 – Disposal Consideration

Waste disposal: Dispose of in a responsible manner. Follow local, state and federal guidelines. Do not discharge into sewers or waterways. Incineration is the preferred method of disposal, although it may be landfilled at an approved facility.

Section 14- Transport Information

DOT Proper Shipping Name: UN1950, Aerosols, 2.1, Limited Quantity

DOT Technical Name: None

DOT Hazard Class: 2.1

UN Number: UN1950

DOT Labels Required (49CFR172.101): LTD QTY

IMDG Shipping Description: UN1950, Aerosols, 2.1, Limited Quantity,

ID Number: UN1950

Hazard Class: 2.1

Packing Group: None

Labels Required: None

Marking Required: Limited Quantity Mark

Placards Required: Limited Quantity

ICAO/IATA

Proper shipping name: Aerosol, Flammable

Hazard Class: 2.1

Identification Number: UN 1950

Packing Group: None

Section 15 – Regulatory Information

Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ: Ethyl Acetate 5000lbs RQ

SARA Hazard Category (311/312): Fire Hazard, Pressure Hazard, Acute Health

Acute Health Yes

Chronic Health star Hazard Yes

Fire Hazard Yes

Sudden release of pressure Yes

Reactive Hazard No

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313:

Dipropylene Glycol Mono Methyl (CAS 34590-94-8), Weight=1-10 % Threshold 1.0%

EPA TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

DSL/NDSL: All components listed

CALIFORNIA PROPOSITION 65: This product is not known to contain listed chemicals.

Section 16 – Other Information:

The information contained herein is based on data considered accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of his product. Therefore, because the product may be used under conditions beyond our control, we assume no liability for its use.