



# LUBE-CUT™

## CUTTING AND TAPPING FLUID

### Aerosol

[WWW.ANTISEIZE.COM](http://WWW.ANTISEIZE.COM)

### **Product Description**

**Lube-Cut™** is a general purpose cutting and tapping fluid in an easy to use and convenient Aerosol Package so it's ready when you are.

**Lube-Cut™** has a foaming action to help it stay in place and cling to your work piece and cutting tools and resists runoff.

**Lube-Cut™** is formulated to work on a variety of metal types and is fortified with cutting fluid additives that function over a wide temperature and pressure range. It has very good adhesion and anti-bonding properties that eliminate dangerous and costly tool breakage. **Lube-Cut™** will extend the life of your cutting tools and reduce sharpening intervals. **Lube-Cut™** is great for those occasional jobs or maintenance operations.

### **Features & Benefits**

- Sulfur free
- Non-staining
- Helps to prevent chip welding
- Cleaner cuts
- Less tool wear and cooler operation
- Reduces friction and wear
- NO Chlorinated solvents
- VOC compliant
- Lubricates and cools cutting points and reduces Tool breakage
- Outperforms average cutting oils
- Guards against rust
- Leaves a thin protective film

### **Applications include**

Tapping tools, threading tools, sawing, cutting, milling, boring, and punching. Suitable for all ferrous metals including aluminum and exotic metals like Titanium and Hastelloy.

### **Typical Properties**

Property	Value
Color	Dark Amber
Odor	Slight Petroleum odor
Specific Gravity	0.9
Viscosity	Foam
RoHS 3	Compliant

### **Cautions**

Read all information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use.

### **GHS compliant**

This product requires GHS pictograms on labels. Refer to Label and SDS for GHS information.

### **Product Limited Warranty**

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

### **Available In:**

**Size:** 18 oz net wt. Aerosol

**P/N:** 17051

**ANTI-SEIZE TECHNOLOGY**

2345 N. 17th AVE. • FRANKLIN PARK, IL 60131-3432

847-455-2300 • [www.antiseize.com](http://www.antiseize.com)