



AST PVR™ Aerosol

WWW.ANTISEIZE.COM

Product Description

AST PVR™ is a thick jelled stripper that quickly dissolves gasket cement, baked on difficult to remove gaskets, carbon deposits. It's a real time saver for Maintenance crews that would otherwise be forced to grind away old deposits and stubborn dried up gasket cements. It saves time and money by eliminating damage caused by excessive scrapping, grinding or chiseling off stuck gaskets which could damage flanges with scrapes, nicks or gouges.

The jelled consistency stays in place and penetrates deep into gasket cements and gasket materials to quickly release them from their flanges or surfaces.

Features & Benefits

- Jelled consistency stays where its sprayed
- Quickly dissolves dried gasket cements and adhesives
- Helps to reduce surface damage caused by tools gouging flange surfaces.
- Non corrosive
- Dissolves asphalt, carbon and other residues
- Easily tackles those hard to remove deposits
- Effectively removes many types of Adhesives
- Removes burned on grease

Directions for use

- 1) Protect any painted surfaces
- 2) Spray on the surface that you want to remove and allow the surface to blister which can take up to 2 minutes
- 3) We recommend using eye protection and wearing solvent resistant gloves when handling this product. Read the warning labels on the can and the SDS Sheet.
- 3) Using a soft edge scrapper, remove the blistered material
- 4) For heavy deposits a second application may be needed

Applications include

Difficult to remove gaskets, Dried Gasket Cements, Dried Adhesives, dissolves built up Asphalt and Tar

Typical Properties

Property	Value
Color	Clear
Specific Gravity	0.9
Vapor Density (air=1)	>1
Water solubility	nil



WARNING: This product can expose you to methylene chloride, which is known to the State of California to cause cancer. For more information go to www.P65warning.ca.gov

Cautions

Do not use as a paint stripper. This product is intended to be used to remove gaskets and gasket cements.

Read all Safety and Warning information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use. Protect surfaces which you do not want to be affected. Solvent resistant glove and eyewear must be worn. Use with adequate ventilation. Do not use in confined areas.

GHS compliant

This product requires GHS pictograms on labels. Refer to Label and SDS for GHS information.

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

SIZE: 18 oz net wt Aerosol can

P/N: 17052