



AST PVR™ Aerosol

WWW.ANTISEIZE.COM

Product Description

AST PVR™ is a fast acting, thick jelled, fast acting paint and varnish stripper. It's a real time saver for Maintenance crews that would otherwise be forced to sand away old paint films and It saves time and money by eliminating damage caused by excessive scrapping, grinding or media blasting. Paint films will quickly bubble up and easily scrapped off or flushed off with water.

Works with primers, paints, polyurethanes, epoxies, latex, oil based paints, shellacs and enamels. Safe for use on wood but use caution on glue joints. Can be used on wood, metal or concrete surfaces. May be used on aluminum, steel, copper, brass and iron. Use caution on magnesium and zinc coated surfaces. Pretesting and inconspicuous area before full scale use.

Features & Benefits

- Jelled consistency stays where its sprayed
- Quickly dissolves dried paints, clear coatings
- Helps to reduce surface damage caused by tools gouging surfaces.
- Non corrosive
- Not combustible
- Easily tackles those hard to remove deposits
- Scrape off blistered film or rinse with water

Directions for use

- 1) Protect any painted surfaces where you do not want the paint removed.
- 2) Spray on the surface that you want to remove and allow the surface to blister which can take up to 15 minutes. Use at temperatures between 65°F to 85°F
- 3) We recommend using eye protection and wearing solvent resistant gloves when handling this product. Use with adequate ventilation. Wear a suitable respirator .Read the warning labels on the can and the SDS Sheet.
- 3) Using a soft edge scrapper, remove the blistered material

- 4) For heavy deposits a second application may be needed

Typical Properties

Property	Value
Color	Clear
Specific Gravity	0.9
Vapor Density (air=1)	>1

Cautions

Read all Safety and Warning information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use. Protect surfaces which you do not want to be affected. Solvent resistant glove and eyewear must be worn. Use with adequate ventilation. Do not use in confined areas.

GHS compliant

[This product requires GHS pictograms on labels.](#)
[Refer to Label and SDS for GHS information.](#)

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

SIZE: 18 oz net wt Aerosol can

P/N: 17052