



SUPER DRY® II

Energized Electrical Cleaner

www.antiseize.com

Product Description

SUPER DRY® II, is a quick-drying, non-flammable solvent degreaser designed to be used on energized electrical equipment or where residual electrical potential exists. The product has a dielectric strength of 45,700 volts and does not allow current creep between components. It also displaces moisture to restore optimum performance.

Spray it on to remove heavy grease, grime and oil instantly from motors, circuits, contacts, . It will not affect conductivity and permits electrical equipment to be cleaned while in use.

SUPER DRY® II dries rapidly and does not leave a film behind, yet it has no flash point and is not ignitable.

Features & Benefits

- Evaporates quickly, leaves no residue
- Non-flammable, non-corrosive
- Displaces moisture
- Quickly cuts through heavy oily films
- Shortens down time for maintenance.
- Dielectric strength of 45,700 volts
- Enables in-place cleaning without disassembly

Applications include

All metals, electric motors, power tools, generators, alternators, contacts, circuit boards (most) switches, solenoids, actuators, brushes, capacitors, transformers, circuit breakers, fuse holders, relays, sensors, speed controllers, motor starters, disconnect switches, outlets, power connectors, contacts, exhaust fan motors and other energized electrical applications.

Typical Properties

Property	Value
Boiling Point	250°F (121°C)
Freeze Point	-9°F (-22.8°C)
Color	Clear liquid
Flash Point	No Flash Point
Specific Gravity	1.6
Weight Per Gallon	13.5lbs/gal
Electrical Conductivity	8×10^{-12}
Toxicity	Group 2A Carcinogen
RoHS	Compliant

Cautions

Read all information on labels and Safety Data Sheets prior to use. This product may require special Personal Protection Equipment. Not recommended in confined areas without adequate ventilation. All products should be tested and evaluated for a particular purpose prior to use. Avoid prolonged contact with some plastics.

GHS compliant

This product requires GHS pictograms on labels.
Refer to Label and SDS for GHS information.

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

Size: 18 oz net wt. aerosol , 5gal pail 55 gal drum
P/N: 17073 53005 53055

NOT FOR SALE IN CALIFORNIA OR DELAWARE