



# PTFE SPRAY HEAVY COAT

## Aerosol

### ANTI SEIZE LUBRICANT AND SEALANT

---

#### **Product Description**

PTFE Spray Heavy Coat is a Dry Film Lubricant coating which contains a generous amount of PTFE and other slip aids along with a binder to lock the PTFE in place.

PTFE Spray Heavy Coat forms a heavy, thick film of PTFE which provides a dry but slippery film which resists abrasion, does not rubs off, and does not attract dirt like an oil or grease will.

PTFE Spray Heavy Coat performs well as a mold release agent and is also beneficial in applications where you need additional slip for sliding surfaces.

#### **Features & Benefits**

- Heavy-Duty dry film Lubricant
- Long lasting Lubrication
- Chemically inert and non-contaminating
- Reduces friction, wear and abrasion
- Excellent corrosion and chemical resistance
- Low coefficient of friction
- Will not attract dirt or dust
- Quick drying
- Bonded adhesion
- Temperatures up to 500°F
- Aerosol is CFC Free and VOC Compliant
- RoHS Compliant

#### **Applications include**

Use as a pipe thread sealant and lubricant, molds, plastic and rubber parts, door and window seals, sliding surfaces, conveyors and chutes, guides and rails, lawn mowers blades and decks, molding dies, casting and stamping dies, automotive, snow removal equipment, construction and mining equipment, gasket coating, thread, Lubricant, bolts and sliding parts, ovens, kilns and many, many other applications.

#### **Cautions**

This product is not recommended for use in oxygen systems. Read all information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use.

#### **GHS compliant**

[This product requires GHS pictograms on labels. Refer to Label and SDS for GHS information.](#)

#### **Product Limited Warranty**

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

#### **Available In:**

**Size: 6 oz net wt. aerosol**

**P/N 17080**

#### **ANTI-SEIZE TECHNOLOGY**

2345 N. 17th AVE. • FRANKLIN PARK, IL 60131-3432

847-455-2300 • [www.antiseize.com](http://www.antiseize.com)