



RED GREASE BEARING LUBRICANT

www.antiseize.com

Product Description

RED GREASE BEARING LUBRICANT meets the growing need for heavy duty, highly adhesive, water resistant grease with very high load carrying capacities. RED GREASE has a highly Tacky Consistency which resists being flung off the bearing at high speeds. Red Grease touts a Timken Load EP rating of over 70 pounds for extreme load carrying capacity. Red Bearing Grease is fortified with polymers which impart excellent adhesion to metal surfaces, and also contains Extreme Pressure Additives and Rust and Oxidation inhibitors for corrosion protection in extreme environments.

Features & Benefits

- Resists water washout, heavy loads and pressures
- Excellent mechanical stability
- Great cold temperature pumpability
- Heavily fortified with rust, oxidation and corrosion inhibiting additives.
- Tacky Consistency and fortified with Extreme Pressure Additives
- Red Color for easy identification for bearings
- Temperature range of -20°F to 250°F (-29°C-135°C)

Applications include

- Bearings
- Disk and Drum brake bearings
- Ball and Roller Bearings
- U-Joints,
- Couplings
- Numerous Industrial and Commercial Bearing applications
- Off Road applications
- Mining, Construction, Agriculture
- Logging, Dredging
- Truck Fleets
- Off Shore Drilling
- Pulp and Paper Machines
- Applications exposed to water, mud and other contaminants
- Superior Performance compared to White Lithium Grease

Product Specifications

Product Data	Typical Values	Test Method
NLGI Grade	2	
Soap Type	Lithium Complex	
Texture	Smooth /Tacky	
Color	Red	
Worked Penetration 60 strokes @77°F	265 – 295	ASTM D217
Dropping Point °F	350°F Min.	ASTM D2265
Oxidation Stability Psi drop/100 hrs. Max.	10	ASTM D942
Wheel Bearing Leakage	5	ASTMD1263Gms
Rust & Corrosion	1,1,1	ASTM D1743
Water Washout 10% 175°F, max.	10%	ASTM D1264
Timken, OK Load Min.	70	ASTM D2509
Base Oil Viscosity		
SUS @100°F	720 – 800	
cSt @100°C	10.5 – 12.5	
cSt @40°C	145 – 185	
Viscosity Index	40	
Pour Point	0	
RoHS	Compliant	

GHS information

The Aerosol version requires GHS Pictograms
The bulk product is considered Non-Hazardous under OSHA HazCom 2012 (GHS) Regulations.

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

Size: 11.25oz aer.	14oz cart	14oz can	5 lb pail	35 lb pail
P/N: 17113	24614	24616	24605	24635

ANTI-SEIZE TECHNOLOGY

2345 N. 17th AVE. • FRANKLIN PARK, IL 60131-3432

847-455-2300 • www.antiseize.com