

PTFE SPRAY LIGHT COAT Aerosol DRY LUBRICANT AND RELEASE AGENT

Product Description

PTFE Spray Light Coat is a multi-purpose, fast drying PTFE (Polytetrafluroethylene) powder lubricant which functions as a dry lubricant which will not attract dirt or dust. It is comprised of PTFE along with a binder to fix the lubricant in place so it resists rub off. PTFE Spray Light Coat is a good alternative to graphite films or silicone sprays in some applications.

PTFE Spray Light Coat has a low coefficient of friction, is chemically inert and is highly resistant to most chemicals. It can be safely used up to 500 F (260 C).

PTFE Spray Light Coat is chemically inert, and an excellent mold release agent with a low coefficient of friction so parts will not stick to it and can be easily removed from the mold.

Features & Benefits

- Dry film Lubricant and release agent
- Long lasting Lubrication
 - Chemically inert and non-contaminating
- Reduces friction, wear and abrasion
- Excellent corrosion and chemical resistance
- Low coefficient of friction
- Will not attract dirt or dust
- Quick drying
- Bonded adhesion
- Temperatures up to 500F
- Aerosol is CFC Free and VOC Compliant
- RoHS Compliant

Applications include

Molds, plastic and rubber parts, door and window seals, sliding surfaces, conveyors and chutes, guides and rails, lawn mowers blades and decks, molding dies, casting and stamping dies, automotive, snow removal equipment, gasket coating, Lubricant, bolts and sliding parts, bicycle chains and many, many other applications.

Cautions

This product is not recommended for use in an oxygen system. Read all information on labels and Safety Data Sheets prior to use. All products should be tested and evaluated for a particular purpose prior to use.

GHS compliant

This product requires GHS pictograms on labels. Refer to Label and SDS for GHS information.

Product Limited Warranty

This information is based on information we believe to be reliable and accurate, but no guarantee of its accuracy is made for a particular application. We urge and recommend that Users pretest their application prior to incorporating the product into use and assume that the User will conduct such testing. Also see warranty statement on website.

Available In:

Size: 12 oz net wt. aerosol

P/N 17075